



WIRING TABLE

P1		P2	
GND	A1	B1	GND
Rx0+	A2	B2	Tx0+
Rx0-	A3	B3	Tx0-
GND	A4	B4	GND
Rx1+	A5	B5	Tx1+
Rx1-	A6	B6	Tx1-
GND	A7	B7	GND
SB	A8	B8	SB
SB	A9	B9	SB
GND	A10		
SB	A11	B10	SB
SB	A12	B11	SB
GND	A13	B12	GND
Rx2+	A14	B13	Tx2+
Rx2-	A15	B14	Tx2-
GND	A16	B15	GND
Rx3+	A17	B16	Tx3+
Rx3-	A18	B17	Tx3-
GND	A19	B18	GND

  

GND	B1	A1	GND
Tx0+	B2	A2	Rx0+
Tx0-	B3	A3	Rx0-
GND	B4	A4	GND
Tx1+	B5	A5	Rx1+
Tx1-	B6	A6	Rx1-
GND	B7	A7	GND
SB	B8	A8	SB
SB	B9	A9	SB
GND	B10		
SB	B11	A10	SB
SB	B12	A11	SB
GND	B13	A12	GND
Tx2+	B14	A13	Rx2+
Tx2-	B15	A14	Rx2-
GND	B16	A15	GND
Tx3+	B17	A16	Rx3+
Tx3-	B18	A17	Rx3-
GND	B19	A18	GND

NOTE:  
 1.100%OPEN&SHORT TESTIGN,  
 2.INSULATION RESISTANCE 10M Ohm MIN DC300V  
 3.CONDUCTIVE RESISTANCE: 2 Ohm MAX

NO.	PART NAME	PART NO.	SPEC DESCRIPTION	QTY	UNIT
9	EXPANDD	AQ-3-MS76001	PET BALCK OD: 10mm	A/R	mm
8	MOLDING	AQ-3-GL10101	LDPE NATURAL	A/R	9
7	ACETATE TAPE	AQ-3-MS77001	W=25±5mm	A/R	mm
6	MOLDING	AQ-3-GL100401	PBT+30GF% BLACK	A/R	9
5	PCB	AQ-3-MS31022	SLIMSAS 4I 38PIN PCB,PIN Au 15u&30u, 88±8 ohm	1	PCS
4	PCB	AQ-3-MS31019	MINISAS 36PIN PCB, PIN15u* Au, 105±10 ohm	1	PCS
3	LATCH	AQ-3-MS21008	STAINLESS STEEL	2	pcs
2	CABLE	AQ-3-MS20101	30AWG CABLE	A/R	mm
1	CABLE	AQ-3-MS40207	SAS4.0,UL20744(32AWG*2C+2D)+AM,BLUE,85±5 ohm	A/R	mm

A	INITIAL RELEASE		20/06/27
REV	DESCRIPTION OF CHANGE		DATE
	TOLERANCE INCHES	M/M	DIKWAN® DONGGGUAN AIQUN INDUSTRIAL CO., LTD.
.X	.015	.30	
.XX	.010	.10	
.XXX	.005	.05	
DRAWN BY	TONY CHAN	SCALE	NONE
		UNIT	MM
CHECK BY		SHEET	1/1
		DATE	22/06/27
CUSTOMFR P/N:		P/N: AQ-1-MS911010500	