



ELECTRICAL CHARACTER:

- a. 100% OPEN&SHORT TESTING;
- b. WITHSTANDING VOLTAGE:DC 300V 0.01Sec;
- c. INSULATION RESISTANCE:10M Ohm(Min);
- d. CONDUCTIVE RESISTANCE:2 Ohm(Max).

A	INITIAL RELEASE		12/10/12
REV	DESCRIPTION OF CHANGE		DATE
TOLERANCE		OIKWAN® DONGGGUAN AIQUN INDUSTRIAL CO., LTD.	
	INCHES	MM	
.X	.015	.30	
.XX	.010	.10	
.XXX	.005	.05	
DRAWN BY	TONY CHAN	SCALE	NONE
CHECK BY		UNIT	MM
		SHEET	1/1
		DATE	16/04/10
		TITLE	MINI SAS 26P TO 26P
CUSTOMER P/N:	P/N: AQ-1-MS221012000		

4	PLASTIC	AQ-3-GL100101	LDPE ROHS	A/R	KG
3	ASSEMBLY PARTS	AQ-3-MS62001	ASSEMBLY PARTS (Zinc ALLOY HOODS, HOOK,PULL-TAB, RUBBER RING)	2	set
2	PCBA	AQ-3-MS31021	MINI SAS 26P PCBA, PIN,15u Au, 100±10 Ohm	2	PCS
1	CABLE	AQ-3-MS41602	(28AWG*2C+D+HMAM+HM)*8C+M+AM+B,DD:7.5±0.15MM,BLACK PVC JACKET 100±5 Ohm	A/R	mm
NO.	PART NAME	PART NO	SPEC DESCRIPTION	QT'Y	UNIT