



. ELECTRICAL CHARACTER:

- a. 100% OPEN&SHORT TESTING;
- b. WITHSTANDING VOLTAGE:DC 300V 0.01Sec;
- c. INSULATION RESISTANCE:10M Ohm(Min);
- d. CONDUCTIVE RESISTANCE:2 Ohm(Max).
- e.Impedance: 85 Ohm
- f.Electrical and mechanical performance should meet the PCIE5.0 industrial standard.

7	LATCH	AQ-3-MS21008	STAINLESS STEEL	2	pcs
6	EXPANDD	AQ-3-MS76001	PET BALCK DD: 10mm	A/R	mm
5	ACETATE TAPE	AQ-3-MS77001	W=25±5mm,BLACK	A/R	mm
4	MOLDING	AQ-3-GL10501	PA,BALCK	A/R	9
3	HUOSING	AQ-3-MS64011	PA66+30%GF,BALCK	2	PCS
2	PCBA	AQ-3-MS31027	MCID 8I PCB, PIN:30u Au, 85±10 ohm	2	PCS
1	CABEL	AQ-3-MS40208	(30AWG*2C+2D)AL+MYLAR,DD:1.0*1.85MM,85±5 ohm	A/R	mm
NO.	PART NAME	PART ND.	SPEC DESCRIPTION	QT'Y	UNIT

TOLERANCE			DIKWAN ® DONGGUAN AIQUN INDUSTRIAL CO., LTD.					
INCHES		M/M						
.X	.015	.30						
.XX	.010	.10	SCALE		NONE		REV	A0
.XXX	.005	.05	UNIT	MM				
DRAWN BY TONY CHAN			SHEET		1/2	COSTOMER:		
CHECK BY LJF			DATE		22/11/06	DWG NO.:AQ03-0219A		
APPD BY			TITLE: MCIO 8I TO 8I CABLE					
CUSIOMER. P/N:			P/N: AQ-1-MSEE1010500					

P1		P2	
A1	GND	B1	GND
A2	TX1+	B2	RX1+
A3	TX1-	B3	RX1-
A4	GND	B4	GND
A5	TX2+	B5	RX2+
A6	TX2-	B6	RX2-
A7	GND	B7	GND
A8	SIDEBAND	B8	SIDEBAND
A9	SIDEBAND	B9	SIDEBAND
A10	GND	B10	GND
A11	SIDEBAND	B11	SIDEBAND
A12	SIDEBAND	B12	SIDEBAND
A13	GND	B13	GND
A14	TX3+	B14	RX3+
A15	TX3-	B15	RX3-
A16	GND	B16	GND
A17	TX4+	B17	RX4+
A18	TX4-	B18	RX4-
A19	GND	B19	GND
A20	TX5+	B20	RX5+
A21	TX5-	B21	RX5-
A22	GND	B22	GND
A23	TX6+	B23	RX6+
A24	TX6-	B24	RX6-
A25	GND	B25	GND
A26	SIDEBAND	B26	SIDEBAND
A27	SIDEBAND	B27	SIDEBAND
A28	GND	B28	GND
A29	SIDEBAND	B29	SIDEBAND
A30	SIDEBAND	B30	SIDEBAND
A31	GND	B31	GND
A32	TX7+	B32	RX7+
A33	TX7-	B33	RX7-
A34	GND	B34	GND
A35	TX8+	B35	RX8+
A36	TX8-	B36	RX8-
A37	GND	B37	GND

P1		P2	
B1	GND	A1	GND
B2	RX1+	A2	TX1+
B3	RX1-	A3	TX1-
B4	GND	A4	GND
B5	RX2+	A5	TX2+
B6	RX2-	A6	TX2-
B7	GND	A7	GND
B8	SIDEBAND	A8	SIDEBAND
B9	SIDEBAND	A9	SIDEBAND
B10	GND	A10	GND
B11	SIDEBAND	A11	SIDEBAND
B12	SIDEBAND	A12	SIDEBAND
B13	GND	A13	GND
B14	RX3+	A14	TX3+
B15	RX3-	A15	TX3-
B16	GND	A16	GND
B17	RX4+	A17	TX4+
B18	RX4-	A18	TX4-
B19	GND	A19	GND
B20	RX5+	A20	TX5+
B21	RX5-	A21	TX5-
B22	GND	A22	GND
B23	RX6+	A23	TX6+
B24	RX6-	A24	TX6-
B25	GND	A25	GND
B26	SIDEBAND	A26	SIDEBAND
B27	SIDEBAND	A27	SIDEBAND
B28	GND	A28	GND
B29	SIDEBAND	A29	SIDEBAND
B30	SIDEBAND	A30	SIDEBAND
B31	GND	A31	GND
B32	RX7+	A32	TX7+
B33	RX7-	A33	TX7-
B34	GND	A34	GND
B35	RX8+	A35	TX8+
B36	RX8-	A36	TX8-
B37	GND	A37	GND

TOLERANCE			INCHES		M/M		DIKWAN® DONGGUAN AIQUN INDUSTRIAL CO., LTD.					
.X	.015	.30					SCALE	NONE		REV	A0	
.XX	.010	.10					UNIT	MM				
.XXX	.005	.05					DRAWN BY	TONY CHAN		SHEET	2/2	COSTOMER:
							CHECK BY	LJF		DATE	22/11/06	DWG NO.:AQ03-0219A
							APPD BY			TITLE: MCIO 8i TO 8i CABLE		
							CUSIOMER. P/N:			P/N: AQ-1-MSEE1010500		