



P1	P2
PIN1	1 CTS
PIN2	2 DSR
PIN3	3 RXD
PIN4	4 GND
PIN5	5 GND
PIN6	6 TXD
PIN7	7 DTR
PIN8	8 RTS

NOTE:
 1.100% OPEN&SHORT TESTING,
 2.INSULATION: 10M Ω hm MIN DC: 300V
 3.CONDUCTIVE: 2 Ω hm MAX
 4.100% FUNCTIONAL TESTING

NO	NAME	Description	QTY	Unit
6	MOLDING	45P PVC, BLUE, MOLDED, ROHS	1	PCS
5	MOLDING	LDPE, , MOLDED, ROHS	A/R	G
4	CONN.	USB TYPE A MALE, ROHS	1	PCS
3	PCB	PCBA WITH FT232+ZT213 CHIP, ROHS	1	PCS
2	CONN.	RJ45 MALE, 8P8C, PIN G/F	1	PCS
1	CABLE	28AWG*8C, BARE COPPER, BLUE PVC JACKET, ROHS	A/R	M

A	INITIAL RELEASE		13/03/02
REV	DESCRIPTION OF CHANGE		DATE
TOLERANCE INCHES			
M/M			
.X	.015	.30	
.XX	.010	.10	
.XXX	.005	.05	
SCALE	NONE		REV
UNIT	MM		A
DRAWN BY	TONY CHAN		SHEET
CHECK BY			1/3
CUSTOMER. P/N:	P/N: AQ-1-RJ10602B1800		COSTOMER:
	DATE		DWG NO.:
	16/9/20		TITLE: USB TO RJ45 CABLE