

Specifications
 Current Rating: 2.5Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding Voltage: 250VAC
 Contact Resistance: 50mΩ Max.
 Operating Temperature: -40° C to +105° C
 Materials
 Contact Material: Bronze
 Insulator Material: High Temperature Thermoplastic, UL 94V-0 LCP or The Equivalent Material
 All Materials Must Meet GREENCONN Hazardous Substances Control Standards.


Ordering Code:

BBF2.54 - M - X - X - X - X - 08

- | | |
|---|---|
| ① Series NO:
2.54mm Board to Board Floating Connector | ⑤ Contact Plating
G0: Gold Flash
G1: 3u" Gold
G2: 5u" Gold
G3: 10u" Gold
G4: 15u" Gold
G5: 30u" Gold
SN: Tin |
| ② M: Male F: Female | ⑥ Packing
T: Tube A: Tray
B: Bag U: Tube+CAP
R: Tape & Reel
W: Tape & Reel+CAP |
| ③ Mating Height:
6.0=6.0mm | ⑦ Serial Number: 08 |
| ④ NO. of Contacts:
See Table
For Example
02:02 Poles | |

Recommended P.C.Board Layout (Tolerance:±0.05)

Unless Otherwise specified tolerance	
X. ±0.35	X.XX: ±0.20
X.X: ±0.25	X.XXX: ±0.15
SCALE: As Shown	UNIT: mm
DRAW Wu Feng Rong	DATE 04/15/2021
CHECK BobYang	DATE 04/15/2021

 ANTENK ELECTRONICS CO., LTD
 Http://www.antenk.com
 E-mail:sales@antenk.com

TITLE:
2.54MM Floating Board to Board Male Plug Connector With Post Mating Hight 6.0mm

DRAWING NO: BBF2.54M-XXXX08
 PRODUCT NO: BBF2.54M-XXXX08



REV	DESCRIPTION	DATE
1	2	3
4	5	6
7	8	