



SPECIFICATIONS

- Voltage rating: 250V AC/DC
- Current rating: 7A AC, DC
- Withstanding Voltage: 1500V AC/minute
- Insulation resistance: 1000MΩ Min
- Temperature range: -40°C~+105°C
- Contact resistance: 10mΩ Max
- Compliant with RoHs and REACH

TERMINAL

- Part NO: AT1561T-xP
- Applicable wire: AWG#18-#24
- Material: Brass or Phosphor Bronze
- Finish: Tin Plated or Gold
- Used in AH1561 series Housing

Ordering information & Specifications

Unit:mm

Part NO.	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
AT1561T-TB	AWG#18-#24	2.70mm(max)	Brass	Tin over Nickel	6,000 PCS
AT1561T-TP	AWG#18-#24	2.70mm(max)	Phosphor Bronze	Tin over Nickel	6,000 PCS
AT1561T-GB	AWG#18-#24	2.70mm(max)	Brass	Gold over Nickel	6,000 PCS
AT1561T-GP	AWG#18-#24	2.70mm(max)	Phosphor Bronze	Gold over Nickel	6,000 PCS

Optional Gold plating available but MOQ requested

Unless Otherwise specified tolerance
 I ±0.35 I, XX: ±0.20
 I, X: ±0.25 I, XXX: ±0.15

SCALE: As Shown UNIT: mm
 DRAW: Jack Bao DATE: 12/15/2017
 CHECK: Bob Yang DATE: 12/15/2017

Antenk ANTENK ELECTRONICS CO., LTD
[Http://www.antenk.com](http://www.antenk.com)
 E-mail:sales@antenk.com

TITLE:7.50-5.00mm pitch Crimp Terminal
 Connector series

DRAWING NO: AT1561T-xP

PRODUCT NO: AT1561T-xP

REV	DESCRIPTION	DATE